



PRODUCT DATA SHEET

FELINE GENUINE LUBRICANTS F5 HYDRAULIC OIL AWS 68

Main Applications

Feline Genuine Lubricants **F5 Super Performance Hydraulic Oil AWS 68** is a supreme quality, formulated with high performance base oil and superior balanced additive system.

F5 specially formulated with premium anti-wear latest additive technology to provide anti-wear protection and thermal stability performance which meets manufacturer requirement for viscosity, oxidation and corrosion protection.

Performance, Features & Benefits

- * Excellent anti-wear performance gives wear protection and reduce down time from unscheduled maintenance.
- * Fully inhibited against rust, oxidation and luster.
- * Fortified with advanced zinc anti-wear additives.
- * Has a high aniline point to minimize attack rubbers.
- * Good durability under heavy operation condition.
- * Excellent water separation and hydrolytic stability means reduced down time through prolonged lubricants life and increased equipment reliability.

Advantages

Feline F5 is the natural choice of machine users who demand maximum engine performance from today's modern vehicles requiring a high level of protection and higher performance oils.

Recommendations for use FELINE F5 – Super Performance Hydraulic Oil AWS 68

Before using the Feline F5 Super performance Hydraulic oil AWS 68, the vehicle's maintenance guide should be checked. Oil changes should be carried out in accordance with the manufacturer's recommendations. The product should not be stored at temperatures over 55°C. It should be kept away from direct sunlight, intense cold and extreme temperature fluctuations. If possible, the packaging should not be exposed to the elements. Otherwise, the drums should be laid horizontally in order to avoid any contamination from water and to prevent the product's label from rubbing off.

Typical Physical Characteristics

Properties	Units	Test Method	Result
Viscosity Grade			AWS 68
Kinematic Viscosity @40°C	cSt	ASTM D445	68
Kinematic Viscosity @100°C	cSt	ASTM D445	9.0
Viscosity Index		ASTM D2270	107
Total Base Number, TBN	mg KOH/g	ASTM D2896	9
Flash Point	°C	ASTM D92	246
Pour Point	°C	ASTM D97	-25
Density @15°C	kg/m ³	ASTM D4052	0.8850
Colour		ASTM D1500	L2.0

These characteristics are typical of current production.

Whilst future production will conform to Feline F5 specification, variations in these characteristics may occur.

Safety and Health Precaution

Contains Petroleum Solvent and Lubricants. Avoid skin and eye contact, especially with used hydraulic oils. Wear protective gloves. Wash hands thoroughly after handling. To protect the environment do not pollute drains, soil and water with used hydraulic oils.

Dispose the containers as per EPA guidelines.

KEEP OUT REACH OF CHILDREN

FELINE GENUINE LUBRICANTS

SELANGOR DARUL EHSAN

MALAYSIA.

Website : www.felinelube.com

Email : felinelube@gmail.com